

April 2, 2002

In response to the Official Action of December 3, 2001 extended for one month to April 3, 2002, please amend this application as follows:

IN THE CLAIMS:

Please rewrite claims 1, 2, 3, 5, 6, and 7 as follows:

At Sub B1 1. (Amended) A telephone network for a structured site, essentially of a business office type, comprising a local computer network connecting computers at the transmitting and receiving ends of the system through network adapters, and telephone sets connected to said telephone network to provide telephone communication between the parties at the transmitting and receiving ends through said local computer network, wherein it is provided with a computer telephony server connected to the local computer network and to a general telephone network, with telephone adapters according to the number of telephone sets, each telephone set being connected, directly through a telephone adapter and a network adapter connected in series thereto, to the local computer network, the telephone adapter being capable of converting

April 2, 2002

analog/digital signals adapted to the clock frequency of the local network, user call signals into addresses of other telephone adapters connected to said local computer network, and hang-up signals.

Sub 17 2. (Amended) A network as claimed in claim 1, wherein at least some of the computers connected to said telephone network are provided with multimedia software to allow direct voice telephone communication

AI Sub B2 3. (Amended) A network as claimed in claim 1, wherein the telephone adapter has a transmission channel and reception channels, the transmission channel having a signal detector-distributor with an input connected to a telephone set, a first output of said signal detector-distributor being connected to the input of a tone dialing recognition device having its output connected to the input of a recognized number transmission device, which has its output connected through the network adapter to the local computer network, a second output of the signal detector-distributor being connected to the input of an analog-to-digital converter having its output connected to the input of a compressor whose output is connected to a processor unit having software to allow exchange

April 2, 2002

Sub B2 } of digital data to be effected within the framework of common network protocols, and the reception channel having a voice and tone signal transmission priority device having its output connected to the telephone set and a first input connected to the output of a call signal dialer, whose input is connected to a call number data converter having its input connected to the local computer network through said network adapter, a second input of the voice and tone signal transmission priority device being connected to the output of a voice signal transmitter, whose input is connected to the output of a decompressor having its input connected to said processor unit.

Sub B3 }
A2 } 5. (Amended) A system to maintain telephone communication between remote structured sites, comprising, at a first site, an internal telephone network including a local computer network to connect computers at the transmitting and receiving ends of the system through network adapters, a computer telephony server connected to the local computer network of said site and to the general telephone network and telephone sets to provide telephone communication between parties at

April 2, 2002

Sub B3
the transmitting and receiving ends through said local computer network, and with telephone adapters according to the number of telephone sets, each telephone set being directly connected, through a telephone adapter, and the network adapter connected in series thereto, to the local computer network, the telephone adapter being capable of converting analog/digital signals adapted to the clock frequency of the local network, user call signals into the addresses of other telephone adapters connected to said local computer network, and hang-up signals, each successive site having an internal telephone network duplicating the internal telephone network of the first site, the local computer network of each site being provided with a router connected thereto and to a router of the local computer network of at least one other site through a communication channel of the computer networks of the remote structured sites.

A2

Sub D17 6. (Amended) A system as claimed in claim 5, wherein at least some of the computers connected to said internal telephone network are provided with multimedia software to allow direct voice telephone

April 2, 2002

communication.

Sub B4
A2
7. (Amended) A system as claimed in claim 5, wherein the telephone adapter has a transmission channel and at least one reception channel, the transmission channel having a signal detector-distributor connected to the input of the telephone set and a first output connected to the input of a tone dialing recognition device, whose output is connected to the input of a recognized number transmission device having its output connected through the network adapter to the local computer network, a second output of the signal detector-distributor being connected to the input of an analog-to-digital converter having its output connected to the input of a compressor whose output is connected to a processor unit provided with software to allow exchange of digital data to be effected within the framework of common network protocols, and one of the reception channels having a voice and tone signal transmission priority device having its output connected to the telephone set and a first input connected to the output of a call signal dialer, which has its input connected to a call number data converter having its input connected

April 2, 2002

B4
A21
through said network adapter to the local computer network, a second input of the voice and tone signal transmission priority device being connected to the output of a voice signal transmitter having its input connected to the output of a digital-to-analog converter having its input connected to the output of a decompressor, whose output is connected to said processor unit.

Sub B5
A3
[Please add the following new claims 9 to 12 as follows:]

9. (New) A telephone network for a structured site, essentially of a business office type, comprising a local computer network connecting computers at the transmitting and receiving ends of the system through network adapters, and telephone sets to provide telephone communication between the parties at the transmitting and receiving ends through said local computer network, including telephone adapters according to the number of telephone sets, each telephone set being connected, directly through a telephone adapter and a network adapter connected in series thereto, to the local computer network, the telephone adapter being capable of converting analog/digital signals adapted to the

April 2, 2002

clock frequency of the local network, user call signals into addresses of other telephone adapters connected to said local computer network, and hang-up signals.

BS
10. (New) The network as claimed in claim 9, wherein the telephone adapter has a transmission channel and at least one reception channel, the transmission channel having a signal detector-distributor with an input connected to a telephone set, a first output of said signal detector-distributor being connected to the input of a tone dialing recognition device having its output connected to the input of a recognized number transmission device, which has its output connected through the network adapter to the local computer network, a second output of the signal detector-distributor being connected to the input of an analog-to-digital converter having its output connected to the input of a compressor whose output is connected to a processor unit having software to allow exchange of digital data to be effected within the framework of common network protocols, and at least one reception channel having a voice and tone signal transmission priority device having its output connected to the

AB

April 2, 2002

BS telephone set and a first input connected to the output of a call signal dialer, whose input is connected to a call number data converter having its input connected to the local computer network through said network adapter, a second input of the voice and tone signal transmission priority device being connected to the output of a voice signal transmitter, whose input is connected to the output of a decompressor having its input connected to said processor unit.

AB
SUBD 11. (New) The network as claimed in claim 10, wherein the digital signals are converted into signals compatible with the network protocol.

12. (New) The network as claimed in claim 9, wherein at least some of the computers connected to said network are provided with multimedia software to allow direct voice telephone communication.
